

DENON

DRA-275RD

AM/FM Stereo Receiver



50W+50W

Video In/Out

SLDC

SIGNAL LEVEL DIVIDED CONSTRUCTION

RadioTEXT



■ Main Features

- RDS (Radio Data System): [PS, PTY, EON-TA, RT, CT]
- Signal Level Divided Construction (S.L.D.C)
- High-Quality Power Amplifier
- Two Sets of Video, Input and Outputs
- Last Function Memory
- 3-Way Speaker Terminals
- A-B Speaker Switching
- Adjustable Loudness
- Switchable AC Outlet
- 40-Station Random Preset Memory
- Auto Preset Memory (FM only)
- Character Input
- Integrated Remote Control
- Rated output: 40 W + 40 W (8 ohms, 20 Hz - 20 kHz, THD 0.05 %),
50 W + 50 W (4 ohms, DIN 1 kHz, THD 0.7 %)
- Signal-to-noise ratio: 78 dB (MM), 95 dB (AUX)
- FM/AM Section/Usable sensitivity: FM: 1.0 μ V, AM: 18 μ V

■ General

- Dimensions: 434 (W) x 142 (H) x 303 (D) mm
- Weight: 5.5 kg

*Design and specifications are subject to change without notice.

NIPPON COLUMBIA CO., LTD.
14-14, AKASAKA 4-CHOME, MINATO-KU, TOKYO 107-8011, JAPAN
Denon Home Page Address: <http://www.denon.co.jp>

21550296 B